

# 

100% RECYCLED PAPER
INSPIRED BY GREEN TECHNOLOGY

Cocoon Silk is a coated recycled paper manufactured using a totally chlorine free process and certified as FSC® 100% recycled.

Cocoon Silk meets the same performance standards as non-recycled paper; with excellent runnability, printability and whiteness (ISO 96).

Cocoon Silk also has an exceptionally high quality surface, which brings out the best in printed images.

100% recycled, 100% white : available in 61# Text to 148# Cover



#### **APPLICATIONS**

Suitable for a wide range of applications (depending on basis weight):

Report and accounts, CSR & environmental reports, brochures, direct mail, art books, catalogues, luxury magazines, greeting cards, invitations, menus etc.

#### **CERTIFICATIONS**





PEFC™ certified available on request

## **Process Chlorine Free**









Fully compatible with all digital presses:





For more in-depth environmental information, please download the Environmental Declaration on www.arjowigginsgraphic.com.

# 100% RECYCLED PAPER INSPIRED BY GREEN TECHNOLOGY

### TECHNICAL SPECIFICATIONS

If you seek information not shown below, contact your local sales office, email <u>julie.brannen@arjowiggins.com</u> or visit <u>www.arjowigginsgraphic.com</u>.

	BASIS WEIGHT	GRAMM AGE	BRIGHTNESS		ODA CITY	CL OCC	CALIDED	D+
			ISO	GE	OPACITY	GLOSS	CALIPER	Pt
	61 TEXT	90	96	92.5	93.5	32	0.0030	3.0
	68 TEXT	100	96	92.5	94	32	0.0033	3.3
	78 TEXT	115	96	92.5	95.5	32	0.0039	3.9
	91 TEXT	135	96	92.5	97	32	0.0045	4.5
	101 TEXT	150	96	92.5	98	32	0.0050	5.0
	115 TEXT	170	96	92.5	99	32	0.0057	5.7
	74 COVER	200	96	92.5	99.5	32	0.0067	6.7
	80 COVER	216	96	92,5	99,5	32	0.0075	7.5
	92 COVER	250	96	92.5	99.5	32	0.0094	9.4
	100 COVER	270	96	92.5	100	32	0.0101	10.1
	111 COVER	300	96	92.5	100	32	0.0112	11.2
	129 COVER	350	96	92.5	100	32	0.0138	13.8
	148 COVER	400	96	92.5	100	32	0.0157	15.7
	100 COVER  111 COVER  129 COVER	270 300 350	96 96 96	92.5 92.5 92.5	100 100 100	32 32 32	0.0101 0.0112 0.0138	10.1 11.2 13.8

### RECOMMENDATIONS

#### Prepress recommendations:

- Screen rulings (Max 200 lpi)
- For heavy ink loads, Under-colour-removal (UCR) recommended

#### Printing recommendations:

- · Guaranteed for Offset litho
- · Suitable for silk screen printing
- Sheets suitable for letter press
- Suitable for use in mono and color laser printers
- Recommended fount solution pH 5.5 +/- 0.5
- Cocoon Silk is suitable for HSWO (heat set web offset):
   keep web temperature to a max. of 150° centigrade
- Compatible with IR-drying and UV-curing
- · Suitable for offset varnishes, acrylic and UV

#### Converting recommendations:

- Suitable for foil lamination, hot-foil blocking / cold foil blocking
- Suitable for blind embossing avoid sharp edges on tools
- Suitable for die cutting
- Folding pre-creasing recommended for >101# Text
- Suitable for clamps, wire thread and adhesive binding, and perforation

This information is supplied in good faith and is accurate at the date of publication. Arjowiggins Graphic reserves the right to change or update information as deemed necessary

Manufactured by:



\_\_\_\_\_graphic papers

